


HEAVY WEIGHT  
NON-WOVEN GEOTEXTILE

GE - 320



SKAPS GE-320 is a needle-punched nonwoven geotextile made of 100% polypropylene staple fibers, which are formed into a random network for dimensional stability. SKAPS GE-320 resists ultraviolet deterioration, rotting, biological degradation, naturally encountered basics and acids. Polypropylene is stable within a pH range of 2 to 13.



SKAPS GE-320 conforms to the physical property values listed below:

Property	Method	English (MARV <sup>2</sup> )	Metric (MARV <sup>2</sup> )
Weight	ASTM D 5261	32 oz/yd <sup>2</sup>	1085 g/m <sup>2</sup>
Grab Tensile Strength	ASTM D 4632	600 lbs	2.66 kN
Grab Elongation	ASTM D 4632	50%	50%
Trapezoid Tear Strength	ASTM D 4533	270 lbs	1.20 kN
CBR Puncture Resistance	ASTM D 6241	2287 lbs	10.17 kN
UV Resistance	ASTM D 4355	70%/500 hrs.	70%/500 hrs.

At time of manufacturing. Handling may change these properties.

*This information is provided for reference purposes only and is not intended as a warranty or guarantee. SKAPS assumes no liability in connection with the use of this information.*